

CIAO AUDIO KIT





#### KCA2061A

# **CIAO KIT AND 2-WIRE MINI WITH HANDSET**





AWARDS

DESIGN MILANO





# KCA2061A

# **CIAO KIT AND 2-WIRE MINI WITH HANDSET**

# **KIT PRODUCTS**



CA2100A 1/2/4/8-BUTTON CIAO ENTRANCE PANEL. S2

GENERAL DATA	
Туре	Monoblock
Product height (inch) (pc)	40.63
Product width (inch) (pc)	23.62
Product depth (inch) (pc)	6.61
Product color	Grey RAL 9006
Material	Technopolymer
Wall-mounted	Yes

# COMPATIBLE SYSTEMS Audio Simplebus 2 with power supply art. 1210/1210A Yes

AUDIO FEATURES	
Microphone	4 (ø), omnidirectional
Loudspeaker	50mm (Ø), 8 Ohm, 0.2W

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Absorption in stand-by (W)	1.7
Maximum absorption (W)	7.6

HARDWARE FEATURES	
Call type	Push-buttons
Type of buttons	Mechanical

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.





# KCA2061A

# CIAO KIT AND 2-WIRE MINI WITH HANDSET

#### HARDWARE FEATURES

Number of push-buttons (n°)	8
Backlight color	White
Clamps	L L COM DO RTE C NO NC SE+ SE-
Removable terminals	Yes
Number of inputs (n°)	2
Number of outputs (n°)	1

SETTINGS	
Loudspeaker volume	Yes
Backlight brightness	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection degree	IP54
IK vandal-proof protection degree	IK08
Operating temperature (°F) (°F)	-13 ÷ 131
Operating humidity (RH max - %) (%)	25 ÷ 95
Environmental class	Ш
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS	
Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes







#### KCA2061A

# CIAO KIT AND 2-WIRE MINI WITH HANDSET

#### 2738W/A SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET

Mini series door-entry phone with handset for Simplebus 2 audio systems. Equipped with a key button, button for additional services such as calls to the porter switchboard..., call volume adjustment, Silent mode (Privacy) and floor call input. Correct positioning of the handset on the base is facilitated by invisible magnetised panels. The additional board art. 2735 is available to purchase separately, for an additional button with voltage free contacts and call repetition.

GENERAL DATA		
Product height (inch) (pc)	44.88	
Product width (inch) (pc)	24.33	
Material	ABS	
Product depth (inch) (pc)	6.61	
Product weight (oz) (oz)	10.58	
Product color	White RAL9003	
COMPATIBLE SYSTEMS		
Audio/video Simplebus 2 with power supply art. 4888CU	Yes	
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes	
Simplebus 2 audio/video kit with power supply art. 1209	Yes	
Audio Simplebus 2 with power supply art. 1210/1210A	Yes	
AUDIO FEATURES		
Technologies implemented	Full-Duplex	

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.





# KCA2061A

CIAO KIT AND 2-WIRE MINI WITH HANDSET		
HARDWARE FEATURES		
Type of buttons	Mechanical	
Service buttons	Lock-release	
Number of inputs (n°)	1	
SETTINGS		
Ringtone volume	Yes	
ENVIRONMENTAL AND COMPLIA	NCE FEATURES	
Operating humidity (RH max - %) (%)	25 ÷ 75	
Environmental class	Ш	
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)	
MAIN FUNCTIONS		
Door opener	Yes	
Actuator control	Yes	
CPS call	Yes	
Outside door call input	Yes	
Silent mode (Privacy)	Yes	
MAIN FEATURES		
Wall-mounted	Yes	
Desk base-mounted	Yes, with a dedicated accessory	
TECHNICAL CHARACTERISTICS		
Supply voltage	22÷35VDC	
Maximum absorption (W)	0.8	
Microphone	9.6 (ø) x 6.9mm, omnidirectional	
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W	
Operating temperature (°F) (°F)	23 ÷ 104	

Technical specifications are subject to change without prior notice and refer to the latest version of the product released.



CIAO AUDIO KIT



#### KCA2061A

# CIAO KIT AND 2-WIRE MINI WITH HANDSET

## **TECHNICAL CHARACTERISTICS**

Clamps

L L CFP CFP



**CIAO AUDIO KIT** 





#### KCA2061A

# CIAO KIT AND 2-WIRE MINI WITH HANDSET

# **CA9210** 2 DOUBLE-HEIGHT BUTTONS FOR CIAO ENTRANCE PANEL



Double-height buttons for use with the Ciao series entrance panel.

# COMPATIBLE SYSTEMS Audio Simplebus 2 with power supply art. 1210/1210A Yes HARDWARE FEATURES Number of push-buttons (n°) 2 ENVIRONMENTAL AND COMPLIANCE FEATURES Operating humidity (RH max - %) (%) 25 ÷ 95 Environmental class III

FEATURES	
Call type	Push-buttons
Material	Polycarbonate Makrolon 2407
Product color	Transparent
Product depth (inch) (pc)	1.85
Product height (inch) (pc)	6.87
Product width (inch) (pc)	11.48
Type of buttons	Mechanical
MAIN FEATURES	
Operating temperature (°F) (°F)	-13 ÷ 131



**CIAO AUDIO KIT** 



#### KCA2061A

# CIAO KIT AND 2-WIRE MINI WITH HANDSET

# CA9213 1 LARGE BUTTON FOR CIAO ENTRANCE PANEL

Large button for use with the Ciao series entrance panel.

# COMPATIBLE SYSTEMSAudio Simplebus 2 with power supply<br/>art. 1210/1210AYesHARDWARE FEATURESNumber of push-buttons (n°)1ENVIRONMENTAL AND COMPLIANCE FEATURESOperating humidity (RH max - %) (%)25 ÷ 95Environmental classIII

FEATURES						
Call type	Push-buttons					
Material	Polycarbonate Makrolon 2407					
Product color	Transparent					
Product depth (inch) (pc)	1.85					
Product height (inch) (pc)	13.87					
Product width (inch) (pc)	11.48					
Type of buttons	Mechanical					
MAIN FEATURES						
Operating temperature (°F) (°F)	-13 ÷ 131					



**CIAO AUDIO KIT** 



#### KCA2061A

# CIAO KIT AND 2-WIRE MINI WITH HANDSET

			1							
	111511				7	1		Ş	ŝ	Aven
	ļ	 	-	-	-					all correct
	à	ŝ	R	5	÷	-	ŝ		3	10000
-										10000

#### 1209 2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one for external unit and one for the monitor power supply. Input voltage 110-240 VAC. Dimensions:  $106 \times 62 \times 89$  mm (6 DIN modules).

MAIN FEATURES								
Supply voltage	110÷240							
Max. current delivered (A)	1.2							
Input connector	Terminal block							
Applicable to DIN rail	Yes							
Number of DIN modules (n°)	6							
GENERAL DATA								
Height (inch) (pc)	14.65							
Width (inch) (pc)	25.04							
Depth (inch) (pc)	21.02							
Type of finish	Plastic							
COMPATIBILITY								
Kit audio/video system	Yes							
ELECTRICAL SPECIFICATIONS								
Maximum power delivered (W)	37							